







**FNR Lever** 



Sync Reverse



Narrow Track Width



Powerful Dual PTO



Metal Face Seals



## **Technical Specifications**

**ENGINE** 

Type

: 36 HP, 2800 RPM, 3 Cylinders, Inline FIP. Coolent Cooled with overflow

reservoir, Naturally Aspirated

Air filter : Dry Type, Dual Element

**TRANSMISSION** 

Clutch : Single

Gear box : 8 Forward + 8 Reverse,

FNR Synch Reverser

Speeds : Forward 1.7 - 20.6 kmph

Reverse 1.7 - 21.5 kmph

**BRAKES** 

Type : Oil Immersed Disc Brakes

**HYDRAULICS** 

Maximum Lift Capacity : 910 kgf

**STEERING** 

Type : Power

**POWER TAKE OFF** 

Type : Independent, 6 Splines Dual PTO : 540 @ 2100 ERPM

: 540 @ 1925 ERPM

WHEELS AND TIRES

Option 1 Front : 6 X 14 Rear : 9.5 X 24 Option 2 Front : 5 X 12 Rear : 8.3 X 24

**FUEL TANK** 

Capacity : 32 L

**ELECTRICAL SYSTEM** 

: 55 Ah, 12V Battery, 50 Amp,

Alternator 12V, 12W Starter Motor

**DIMENSION AND WEIGHT** 

Total Weight : 1200 kg

Turning Radius with Brakes : 2300 mm Turning Radius without Brakes : 3000 mm

**ACCESSORIES\*** 

- Ballast Weight - Wagon hitch

**FACTORY FITTED OPTIONS** 

Roll Over Protection System (ROPS) Seat and Seat Belt

**FEATURES** 

- Sync Reverser - Finger Guard - FNR NSS

- Radiator Screen - Water Seperator - Digital hour meter

- Underhood with downdraft exhaust muffler

- Metal Face Seals

Note: All options / features may not be available for single variant. Cardan Shaft Cover diameter more than 165 mm should not be used with 995mm setting (i.e with 5 X 12 & 8.3 X 24 tires)



\*\*Width specifications with 6 X 14 Front tires and 9.5 X 24 Rear tires

John Deere Genuine Parts

| Economical | Reliable | Easily available|



John Deere Asia (Singapore) Private Limited 438 Alexandra Road #12-01/04 Alexandra Point, Singapore 119958

